

# Package: miniCRAN (via r-universe)

October 14, 2026

**Version** 0.3.1.9000

**License** GPL-2

**Copyright** Andrie de Vries, Microsoft Corporation

**Title** Create a Mini Version of CRAN Containing Only Selected Packages

**Description** Makes it possible to create an internally consistent repository consisting of selected packages from CRAN-like repositories. The user specifies a set of desired packages, and 'miniCRAN' recursively reads the dependency tree for these packages, then downloads only this subset. The user can then install packages from this repository directly, rather than from CRAN. This is useful in production settings, e.g. server behind a firewall, or remote locations with slow (or zero) Internet access.

**URL** <https://github.com/andrie/miniCRAN>

**BugReports** <https://github.com/andrie/miniCRAN/issues>

**Imports** graphics, httr, methods, stats, tools, utils, igraph, assertthat (>= 0.2.0)

**Suggests** devtools, knitr, rmarkdown, testthat (>= 2.1.0), covr, withr, mockery, testthis, roxygen2, mockr, spelling

**LazyData** true

**LazyLoad** true

**VignetteBuilder** knitr

**RoxygenNote** 7.3.1

**Roxygen** list(markdown = TRUE)

**Encoding** UTF-8

**Language** en-US

**Config/testthat/edition** 3

**Config/pak/sysreqs** libglpk-dev libxml2-dev libssl-dev

**Repository** <https://andrie.r-universe.dev>

**Date/Publication** 2026-05-15 15:37:15 UTC

```
RemoteUrl https://github.com/andrie/minicran
RemoteRef HEAD
RemoteSha e50806eb7b1e6bf3c98533481ef40acfcfd69694
```

Contents

|                                   |           |
|-----------------------------------|-----------|
| miniCRAN-package . . . . .        | 2         |
| .listFiles . . . . .              | 4         |
| addLocalPackage . . . . .         | 5         |
| addOldPackage . . . . .           | 6         |
| addPackage . . . . .              | 9         |
| addPackageListingGithub . . . . . | 11        |
| basePkgs . . . . .                | 12        |
| checkVersions . . . . .           | 13        |
| cranJuly2014 . . . . .            | 15        |
| getCranDescription . . . . .      | 15        |
| is.online . . . . .               | 16        |
| makeDepGraph . . . . .            | 16        |
| makeLibrary . . . . .             | 18        |
| makeRepo . . . . .                | 18        |
| pkgAvail . . . . .                | 21        |
| pkgDep . . . . .                  | 22        |
| plot.pkgDepGraph . . . . .        | 23        |
| repoPrefix . . . . .              | 25        |
| twodigitRversion . . . . .        | 26        |
| updatePackages . . . . .          | 27        |
| <b>Index</b>                      | <b>30</b> |

---

|                  |                    |
|------------------|--------------------|
| miniCRAN-package | <i>description</i> |
|------------------|--------------------|

---

Description

At the end of 2014, CRAN consisted of more than 6,000 packages. Many organisations need to maintain a private mirror of CRAN, but with only a subset of packages that are relevant to them.

Details

miniCRAN makes it possible to create an internally consistent repository consisting of selected packages from CRAN-like repositories. The user specifies a set of desired packages, and miniCRAN recursively reads the dependency tree for these packages, then downloads only this subset.

There are many reasons for not creating a complete mirror CRAN using rsync:

- You may wish to mirror only a subset of CRAN, for security, legal compliance or any other in-house reason

- You may wish to restrict internal package use to a subset of public packages, to minimize package duplication, or other reasons of coding standards
- You may wish to make packages available from public repositories other than CRAN, e.g. BioConductor, r-forge, OmegaHat, etc.
- You may wish to add custom in-house packages to your repository

The ambition of miniCRAN is to eventually satisfy all of these considerations.

### Making a private repo

- `pkgAvail()`: Read from a local (or remote) CRAN-like repository and determine available packages.
- `pkgDep()`: Find (recursive) package dependencies.
- `makeRepo()` : Make a mini CRAN repository, by downloading packages (and their dependencies) and creating the appropriate file structure for a repository. This allows you to use functions like `utils::available.packages()` and `utils::install.packages()` on your local repository.

This subset will be internally consistent, i.e. the following functions will work as expected:

- `utils::available.packages()`
- `utils::install.packages()`

The main function is `makeRepo()` - this will download all the required packages, with their dependencies, into the appropriate repository file structure, and then create the repository index (PACKAGES) file.

### Updating packages in a repo

- `oldPackages()`: Indicates packages which have a (suitable) later version on the repositories
- \* `updatePackages()`: Offers to download and install such packages

### Creating dependencies

To get a recursive list of dependencies as well as a plot, use `pkgDep()` followed by `makeDepGraph()`.

- `pkgDep()`: Find (recursive) package dependencies.
- `makeDepGraph()`: Create graph of selected package dependencies.
- `plot.pkgDepGraph()`: Create a visualization of the dependency graph

### Package options

`minicran.mran` preferred p3m URL. Defaults to <https://packagemanager.posit.co/cran> for R versions 3.2.2 and greater. Versions earlier than 3.2.2 use HTTP instead of HTTPS.

**Author(s)**

**Maintainer:** Andrie de Vries <apdevries@gmail.com> [copyright holder]

Other contributors:

- Alex Chubaty <alex.chubaty@gmail.com> [contributor]
- Microsoft Corporation [copyright holder]

**See Also**

Useful links:

- <https://github.com/andrie/miniCRAN>
- Report bugs at <https://github.com/andrie/miniCRAN/issues>

---

.listFiles

*List pre-built packages in a directory based on file extension*

---

**Description**

List pre-built packages in a directory based on file extension

**Usage**

```
.listFiles(pkgs, path, type)
```

**Arguments**

|      |                                                                             |
|------|-----------------------------------------------------------------------------|
| pkgs | Character vector of package names                                           |
| path | Character string specifying the directory containing packages to be added.  |
| type | Character indicating the package type (e.g., "source", "win.binary", etc.). |

**Value**

Installs the packages and returns the new package index.

**Examples**

```
## Not run:
.listFiles('path/to/my/packages', type = "source")

## End(Not run)
```

---

|                 |                                                     |
|-----------------|-----------------------------------------------------|
| addLocalPackage | <i>Add local packages to a miniCRAN repository.</i> |
|-----------------|-----------------------------------------------------|

---

## Description

Examine the contents of a directory specified by `pkgPath` for pre-built packages matching the names specified by `pkgs`, and add these to the miniCRAN repository.

## Usage

```
addLocalPackage(
  pkgs = NULL,
  pkgPath = NULL,
  path = NULL,
  type = "source",
  Rversion = R.version,
  writePACKAGES = TRUE,
  deps = FALSE,
  quiet = FALSE,
  build = FALSE
)
```

## Arguments

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>pkgs</code>          | Character vector of packages to download                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>pkgPath</code>       | Character vector of directory location containing packages to be added. Note that <code>pkgPath</code> should be the parent directory of the package (i.e., the package directory path is constructed from <code>file.path(pkgPath, pkgs)</code> ).                                                                                                                                                                                                                   |
| <code>path</code>          | Destination download path. This path is the root folder of your new repository.                                                                                                                                                                                                                                                                                                                                                                                       |
| <code>type</code>          | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                                                          |
| <code>Rversion</code>      | Version of R (only used if <code>type</code> is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components <code>major</code> and <code>minor</code></li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| <code>writePACKAGES</code> | If TRUE, calls <a href="#">write_PACKAGES()</a> to update the repository PACKAGES file.                                                                                                                                                                                                                                                                                                                                                                               |
| <code>deps</code>          | Not used. See note.                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>quiet</code>         | If TRUE, suppress status messages (if any), and the progress bar during download.                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>build</code>         | Logical indicating whether packages should be build prior to adding.                                                                                                                                                                                                                                                                                                                                                                                                  |

**Details**

To build a package from source and then add it, use `build = TRUE`. Note that package development libraries and the `devtools` package must be installed on your system in order to build packages.

**Value**

Installs the packages and returns the new package index.

**Note**

Currently, adding local packages does not check nor download their dependencies.

**Author(s)**

Alex Chubaty

**Examples**

```
## Not run:
addLocalPackage("myPackage", "path/to/my/prebuilt/package",
               "path/to/my/miniCRAN/repo")

addLocalPackage("myPackage", "path/to/my/package/sourcecode",
               "path/to/my/miniCRAN/repo", build = TRUE)

## End(Not run)
```

---

addOldPackage

*Add old package versions to a miniCRAN repository.*

---

**Description**

Will download and add older source package versions. Older binary versions are not normally available on CRAN and should be built from source on the platform for which they are required. As such, specifying `type!="source"` will likely fail as the download will not be successful.

**Usage**

```
addOldPackage(
  pkgs = NULL,
  path = NULL,
  vers = NULL,
  repos = getOption("repos"),
  type = "source",
  Rversion = R.version,
  writePACKAGES = TRUE,
  deps = FALSE,
  quiet = TRUE
)
```

**Arguments**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs          | Character vector of packages to download                                                                                                                                                                                                                                                                                                                                                                                       |
| path          | Destination download path. This path is the root folder of your new repository.                                                                                                                                                                                                                                                                                                                                                |
| vers          | The package version to install.                                                                                                                                                                                                                                                                                                                                                                                                |
| repos         | URL(s) of the 'contrib' sections of the repositories, e.g. "https://cran.us.r-project.org". Passed to <a href="#">available.packages()</a>                                                                                                                                                                                                                                                                                     |
| type          | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                   |
| Rversion      | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| writePACKAGES | If TRUE, calls <a href="#">write_PACKAGES()</a> to update the repository PACKAGES file.                                                                                                                                                                                                                                                                                                                                        |
| deps          | logical indicating whether the package dependencies should be added (default TRUE).                                                                                                                                                                                                                                                                                                                                            |
| quiet         | If TRUE, suppress status messages (if any), and the progress bar during download.                                                                                                                                                                                                                                                                                                                                              |

**Value**

Adds the packages, rebuilds the package index, and invisibly returns the number of packages written to the index files.

**Note**

Dependencies for old package versions cannot be determined automatically and must be specified by the user in pkgs and vers. Thus, deps=FALSE is the default for this function.

**See Also**

Other update repo functions: [addPackage\(\)](#), [checkVersions\(\)](#), [makeRepo\(\)](#), [updatePackages\(\)](#)

**Examples**

```
### `checkVersions` and `add.packages.miniCRAN` require an existing miniCRAN repo

# Specify list of packages to download
mirror <- c(CRAN = "https://cloud.r-project.org")
mirror
pkgs <- c("foreach")
pkgTypes <- c("source", "win.binary")

if (interactive()) {
```

```

    if (!is.online()) {
      message("p3m seems to be not available. Check your internet connection.")
    } else {
      pdb <- pkgAvail(repos = mirror, type = "source")
    }
  } else {
    pdb <- cranJuly2014
  }

  if (interactive()) {
    if (!is.online()) {
      message("p3m seems to be not available. Check your internet connection.")
    } else {
      pkgList <- pkgDep(pkgs, availPkgs = pdb, repos = mirror, type = "source", suggests = FALSE)
      pkgList
    }
  }

  # Create temporary folder for miniCRAN

  if (interactive()) {
    if (!is.online()) {
      message("p3m seems to be not available. Check your internet connection.")
    } else {
      dir.create(pth <- file.path(tempdir(), "miniCRAN"))

      # Make repo for source and win.binary
      makeRepo(pkgList, path = pth, repos = mirror, type = pkgTypes)

      # Add other versions of a package (and assume these were added previously)
      oldVers <- data.frame(
        package = c("foreach", "codetools", "iterators"),
        version = c("1.4.0", "0.2-7", "1.0.5"),
        stringsAsFactors = FALSE
      )
      pkgs <- oldVers$package
      addOldPackage(pkgs, path = pth, vers = oldVers$version, repos = mirror, type = "source")
      # NOTE: older binary versions would need to be build from source

      # List package versions in the miniCRAN repo (produces warning about duplicates)
      pkgVersionsSrc <- checkVersions(pkgs, path = pth, type = "source")
      pkgVersionsBin <- checkVersions(pkgs, path = pth, type = "win.binary")

      # After inspecting package versions, remove old versions
      basename(pkgVersionsSrc$source) # "foreach_1.4.0.tar.gz" "foreach_1.4.2.tar.gz"
      basename(pkgVersionsBin$win.binary) # "foreach_1.4.0.zip" "foreach_1.4.2.zip"
      file.remove(c(pkgVersionsSrc$source[1], pkgVersionsBin$win.binary[1]))

      # Rebuild package index after adding/removing files
      updateRepoIndex(pth, type = pkgTypes, Rversion = R.version)

      pkgAvail(pth, type = "source")
    }
  }

```

```

# Add new packages (from CRAN) to the miniCRAN repo
addPackage("Matrix", path = pth, repos = mirror, type = pkgTypes)

# Delete temporary folder
unlink(pth, recursive = TRUE)
}
}

```

---

addPackage

Add packages to a miniCRAN repository.

---

## Description

Add packages to a miniCRAN repository.

## Usage

```

addPackage(
  pkgs = NULL,
  path = NULL,
  repos = getOption("repos"),
  type = "source",
  Rversion = R.version,
  writePACKAGES = TRUE,
  deps = TRUE,
  quiet = FALSE
)

```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs          | Character vector of packages to download                                                                                                                                                                                                                                                                                                                                                                                       |
| path          | Destination download path. This path is the root folder of your new repository.                                                                                                                                                                                                                                                                                                                                                |
| repos         | URL(s) of the 'contrib' sections of the repositories, e.g. "https://cran.us.r-project.org". Passed to <a href="#">available.packages()</a>                                                                                                                                                                                                                                                                                     |
| type          | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                   |
| Rversion      | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| writePACKAGES | If TRUE, calls <a href="#">write_PACKAGES()</a> to update the repository PACKAGES file.                                                                                                                                                                                                                                                                                                                                        |

|       |                                                                                     |
|-------|-------------------------------------------------------------------------------------|
| deps  | logical indicating whether the package dependencies should be added (default TRUE). |
| quiet | If TRUE, suppress status messages (if any), and the progress bar during download.   |

**Value**

Installs the packages, rebuilds the package index, and invisibly returns the number of packages written to the index files.

**See Also**

Other update repo functions: [addOldPackage\(\)](#), [checkVersions\(\)](#), [makeRepo\(\)](#), [updatePackages\(\)](#)

**Examples**

```
### `checkVersions` and `add.packages.miniCRAN` require an existing miniCRAN repo

# Specify list of packages to download
mirror <- c(CRAN = "https://cloud.r-project.org")
mirror
pkgs <- c("foreach")
pkgTypes <- c("source", "win.binary")

if (interactive()) {
  if (!is.online()) {
    message("p3m seems to be not available. Check your internet connection.")
  } else {
    pdb <- pkgAvail(repos = mirror, type = "source")
  }
} else {
  pdb <- cranJuly2014
}

if (interactive()) {
  if (!is.online()) {
    message("p3m seems to be not available. Check your internet connection.")
  } else {
    pkgList <- pkgDep(pkgs, availPkgs = pdb, repos = mirror, type = "source", suggests = FALSE)
    pkgList
  }
}

# Create temporary folder for miniCRAN

if (interactive()) {
  if (!is.online()) {
    message("p3m seems to be not available. Check your internet connection.")
  } else {
    dir.create(pth <- file.path(tempdir(), "miniCRAN"))
  }
}
```

```

# Make repo for source and win.binary
makeRepo(pkgList, path = pth, repos = mirror, type = pkgTypes)

# Add other versions of a package (and assume these were added previously)
oldVers <- data.frame(
  package = c("foreach", "codetools", "iterators"),
  version = c("1.4.0", "0.2-7", "1.0.5"),
  stringsAsFactors = FALSE
)
pkgs <- oldVers$package
addOldPackage(pkgs, path = pth, vers = oldVers$version, repos = mirror, type = "source")
# NOTE: older binary versions would need to be build from source

# List package versions in the miniCRAN repo (produces warning about duplicates)
pkgVersionsSrc <- checkVersions(pkgs, path = pth, type = "source")
pkgVersionsBin <- checkVersions(pkgs, path = pth, type = "win.binary")

# After inspecting package versions, remove old versions
basename(pkgVersionsSrc$source) # "foreach_1.4.0.tar.gz" "foreach_1.4.2.tar.gz"
basename(pkgVersionsBin$win.binary) # "foreach_1.4.0.zip" "foreach_1.4.2.zip"
file.remove(c(pkgVersionsSrc$source[1], pkgVersionsBin$win.binary[1]))

# Rebuild package index after adding/removing files
updateRepoIndex(pth, type = pkgTypes, Rversion = R.version)

pkgAvail(pth, type = "source")

# Add new packages (from CRAN) to the miniCRAN repo
addPackage("Matrix", path = pth, repos = mirror, type = pkgTypes)

# Delete temporary folder
unlink(pth, recursive = TRUE)
}
}

```

---

addPackageListingGithub

*Add DESCRIPTION information from package on github.*

---

## Description

Downloads the DESCRIPTION file from a package on github, parses the fields and adds (or replaces) a row in the available package database.

## Usage

```

addPackageListingGithub(
  pdb = pkgAvail(),
  repo,
  username = NULL,

```

```
    branch = "main"
  )
```

### Arguments

|          |                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------|
| pdb      | Package database, usually the result of <a href="#">pkgAvail()</a> or <a href="#">available.packages()</a> |
| repo     | Character vector. Name of repository on github, e.g. "andrie/rrd"                                          |
| username | Optional character vector. Name of repository on github, e.g. "andrie/rrd"                                 |
| branch   | name of branch, defaults to "main"                                                                         |

### Examples

```
# Create package database
pdb <- cranJuly2014

if (interactive()) {
  pdb <- pkgAvail(repos = c(CRAN = "https://cloud.r-project.org"))

  # Overwrite pdb with development version of miniCRAN at github
  newpdb <- addPackageListingGithub(pdb = pdb, "andrie/miniCRAN")
  newpdb["miniCRAN", ]

  # Add package from github that's not currently on CRAN
  newpdb <- addPackageListingGithub(pdb = pdb, repo = "tidyverse/ggplot2", branch = "main")
  newpdb["ggplot2", ]

  set.seed(1)
  plot(makeDepGraph("ggplot2", availPkgs = newpdb, suggests = TRUE))
}
```

---

|          |                                        |
|----------|----------------------------------------|
| basePkgs | <i>Returns names of base packages.</i> |
|----------|----------------------------------------|

---

### Description

Retrieves names of installed packages by calling [utils::installed.packages\(\)](#) and returning only those packages where `Priority == "base"`.

### Usage

```
basePkgs()
```

### See Also

[pkgDep\(\)](#)

Other dependency functions: [makeDepGraph\(\)](#), [pkgDep\(\)](#), [plot.pkgDepGraph\(\)](#)

---

|               |                                                                          |
|---------------|--------------------------------------------------------------------------|
| checkVersions | <i>Check for previous versions of packages in a miniCRAN repository.</i> |
|---------------|--------------------------------------------------------------------------|

---

## Description

Checks for previous versions, and returns the file paths for packages with multiple versions. You can subsequently decide which version to keep.

## Usage

```
checkVersions(pkgs = NULL, path = NULL, type = "source", Rversion = R.version)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs     | Character vector of packages to be installed. If not provided, checks all files for multiple package versions.                                                                                                                                                                                                                                                                                                                 |
| path     | The local path to the directory where the miniCRAN repo resides.                                                                                                                                                                                                                                                                                                                                                               |
| type     | character, indicating the type of package to download and install. See <a href="#">install.packages()</a> .                                                                                                                                                                                                                                                                                                                    |
| Rversion | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |

## Value

Returns invisibly the file paths to packages with multiple versions for removal.

list with an element for each type, consisting of a character vector of download paths

## See Also

Other update repo functions: [addOldPackage\(\)](#), [addPackage\(\)](#), [makeRepo\(\)](#), [updatePackages\(\)](#)

## Examples

```
### `checkVersions` and `add.packages.miniCRAN` require an existing miniCRAN repo

# Specify list of packages to download
mirror <- c(CRAN = "https://cloud.r-project.org")
mirror
pkgs <- c("foreach")
pkgTypes <- c("source", "win.binary")

if (interactive()) {
  if (!is.online()) {
```

```

    message("p3m seems to be not available. Check your internet connection.")
  } else {
    pdb <- pkgAvail(repos = mirror, type = "source")
  }
} else {
  pdb <- cranJuly2014
}

if (interactive()) {
  if (!is.online()) {
    message("p3m seems to be not available. Check your internet connection.")
  } else {
    pkgList <- pkgDep(pkgs, availPkgs = pdb, repos = mirror, type = "source", suggests = FALSE)
    pkgList
  }
}

# Create temporary folder for miniCRAN

if (interactive()) {
  if (!is.online()) {
    message("p3m seems to be not available. Check your internet connection.")
  } else {
    dir.create(pth <- file.path(tempdir(), "miniCRAN"))

    # Make repo for source and win.binary
    makeRepo(pkgList, path = pth, repos = mirror, type = pkgTypes)

    # Add other versions of a package (and assume these were added previously)
    oldVers <- data.frame(
      package = c("foreach", "codetools", "iterators"),
      version = c("1.4.0", "0.2-7", "1.0.5"),
      stringsAsFactors = FALSE
    )
    pkgs <- oldVers$package
    addOldPackage(pkgs, path = pth, vers = oldVers$version, repos = mirror, type = "source")
    # NOTE: older binary versions would need to be build from source

    # List package versions in the miniCRAN repo (produces warning about duplicates)
    pkgVersionsSrc <- checkVersions(pkgs, path = pth, type = "source")
    pkgVersionsBin <- checkVersions(pkgs, path = pth, type = "win.binary")

    # After inspecting package versions, remove old versions
    basename(pkgVersionsSrc$source) # "foreach_1.4.0.tar.gz" "foreach_1.4.2.tar.gz"
    basename(pkgVersionsBin$win.binary) # "foreach_1.4.0.zip" "foreach_1.4.2.zip"
    file.remove(c(pkgVersionsSrc$source[1], pkgVersionsBin$win.binary[1]))

    # Rebuild package index after adding/removing files
    updateRepoIndex(pth, type = pkgTypes, Rversion = R.version)

    pkgAvail(pth, type = "source")
  }
}

```

```

# Add new packages (from CRAN) to the miniCRAN repo
addPackage("Matrix", path = pth, repos = mirror, type = pkgTypes)

# Delete temporary folder
unlink(pth, recursive = TRUE)
}
}

```

cranJuly2014

*Stored version of available.packages()***Description**

Copy of the result of `utils::available.packages()` on July 1, 2014.

**Usage**

```
cranJuly2014
```

**Format**

```
matrix
```

getCranDescription

*Obtains DESCRIPTION metadata from CRAN for each package.***Description**

This is a wrapper around `tools::CRAN_package_db` and may be deprecated in future versions of the package.

**Usage**

```

getCranDescription(
  pkg,
  repos = getOption("repos"),
  type = "source",
  pkgs = pkgDep(pkg, repos = repos, type = type)
)

```

**Arguments**

|                    |                                                                                                                                                                                                           |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>pkg</code>   | Character vector of packages.                                                                                                                                                                             |
| <code>repos</code> | URL(s) of the 'contrib' sections of the repositories, e.g. <code>"https://cran.us.r-project.org"</code> . Passed to <code>available.packages()</code>                                                     |
| <code>type</code>  | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <code>download.packages()</code> . |
| <code>pkgs</code>  | Character vector of packages to download                                                                                                                                                                  |

**Examples**

```

if (interactive()) {
  getCranDescription(c("igraph", "ggplot2", "XML"),
                    repos = c(CRAN = getOption("minicran.mran")))
}

```

---

|           |                                              |
|-----------|----------------------------------------------|
| is.online | Returns TRUE if the p3m URL can be accessed. |
|-----------|----------------------------------------------|

---

**Description**

Returns TRUE if the p3m URL can be accessed.

**Usage**

```
is.online(url = NULL, tryHttp = TRUE)
```

**Arguments**

|         |                                                                             |
|---------|-----------------------------------------------------------------------------|
| url     | p3m url                                                                     |
| tryHttp | If TRUE, also attempts http URL, for compatibility with older versions of R |

---

|              |                                                  |
|--------------|--------------------------------------------------|
| makeDepGraph | Create dependency graph from available packages. |
|--------------|--------------------------------------------------|

---

**Description**

Each package is a node, and a dependency is an edge

**Usage**

```

makeDepGraph(
  pkg,
  availPkgs,
  repos = getOption("repos"),
  type = "source",
  suggests = TRUE,
  enhances = FALSE,
  includeBasePkgs = FALSE,
  ...
)

```

**Arguments**

|                              |                                                                                                                                                                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>pkg</code>             | Character vector of packages.                                                                                                                                                                                                                         |
| <code>availPkgs</code>       | Data frame with an element called <code>package</code> . The <code>package</code> element is a vector of available packages. Defaults to reading this list from CRAN, using <a href="#">available.packages()</a>                                      |
| <code>repos</code>           | URL(s) of the 'contrib' sections of the repositories, e.g. <code>"https://cran.us.r-project.org"</code> . Passed to <a href="#">available.packages()</a>                                                                                              |
| <code>type</code>            | Possible values are (currently) <code>"source"</code> , <code>"mac.binary"</code> and <code>"win.binary"</code> : the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> . |
| <code>suggests</code>        | If TRUE, retrieves Suggests dependencies (non-recursively)                                                                                                                                                                                            |
| <code>enhances</code>        | If TRUE, retrieves Enhances dependencies (non-recursively)                                                                                                                                                                                            |
| <code>includeBasePkgs</code> | If TRUE, include base R packages in results                                                                                                                                                                                                           |
| <code>...</code>             | Other arguments passed to <a href="#">available.packages()</a>                                                                                                                                                                                        |

**See Also**

[pkgDep\(\)](#) to extract package dependencies

Other dependency functions: [basePkgs\(\)](#), [pkgDep\(\)](#), [plot.pkgDepGraph\(\)](#)

**Examples**

```
if (interactive()) {
  availPkgs <- cranJuly2014

  availPkgs <- pkgAvail(
    repos = c(CRAN = "https://cloud.r-project.org"),
    type = "source"
  )

  # Create dependency graph using stored database of available packages
  p <- makeDepGraph(
    c("ggplot2", "forecast"),
    availPkgs = availPkgs
  )

  if(require(igraph)) plot(p)

  # Create dependency graph using newly retrieved database from CRAN

  p <- makeDepGraph(
    c("ggplot2", "forecast"),
    repos = c(CRAN = getOption("minicran.mran")),
    type = "source"
  )
  if(requireNamespace("igraph", quietly = TRUE)) {
    plot(p)
  }
}
```

```

    } else {
      message("install package `igraph` to view dependency graph")
    }
  }
}

```

---

makeLibrary

*Deprecated function to download packages to local folder.*


---

### Description

Deprecated function to download packages to local folder.

### Usage

```
makeLibrary(pkgs, path, type = "source")
```

### Arguments

|      |                                                                                                                                                                                                              |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs | Character vector of packages to download                                                                                                                                                                     |
| path | Destination download path. This path is the root folder of your new repository.                                                                                                                              |
| type | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> . |

---

makeRepo

*Downloads packages from CRAN to specified path and creates a local repository.*


---

### Description

Given a list of packages, downloads these packages to a specified destination folder using the required CRAN folder structure, and finally creates the PACKAGES index file. Since the folder structure mimics the required structure and files of a CRAN repository, it supports functions like [utils::install.packages\(\)](#).

### Usage

```

makeRepo(
  pkgs,
  path,
  repos = getOption("repos"),
  type = "source",
  Rversion = R.version,
  download = TRUE,

```

```

    writePACKAGES = TRUE,
    filters = NULL,
    quiet = FALSE
  )

  updateRepoIndex(path, type = "source", Rversion = R.version)

```

## Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs          | Character vector of packages to download                                                                                                                                                                                                                                                                                                                                                                                       |
| path          | Destination download path. This path is the root folder of your new repository.                                                                                                                                                                                                                                                                                                                                                |
| repos         | URL(s) of the 'contrib' sections of the repositories, e.g. "https://cran.us.r-project.org".<br>Passed to <a href="#">available.packages()</a>                                                                                                                                                                                                                                                                                  |
| type          | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms.<br>Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                |
| Rversion      | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| download      | If TRUE downloads packages.                                                                                                                                                                                                                                                                                                                                                                                                    |
| writePACKAGES | If TRUE, calls <a href="#">write_PACKAGES()</a> to update the repository PACKAGES file.                                                                                                                                                                                                                                                                                                                                        |
| filters       | passed to <a href="#">utils::available.packages</a>                                                                                                                                                                                                                                                                                                                                                                            |
| quiet         | If TRUE, suppress status messages (if any), and the progress bar during download.                                                                                                                                                                                                                                                                                                                                              |

## Value

character vector of downloaded package files

## Repo folder structure

A repository has two main folders, one for source packages, and the other for binary packages. Inside the binary package folder, bin, you will find subfolders for Windows as well as the various OSX binaries.

```

+- Root
...+- src/contrib
.....+- PACKAGES
..+- bin
.....+- windows/contrib/version
.....+- PACKAGES
.....+- macosx/contrib/version

```

```

.....+- PACKAGES
.....+- macosx/mavericks/contrib/version
.....+- PACKAGES
.....+- macosx/leopard/contrib/version
.....+- PACKAGES

```

### Note

Internally makes use of `utils::download.packages()` and `write_PACKAGES()`

### See Also

Other update repo functions: `addOldPackage()`, `addPackage()`, `checkVersions()`, `updatePackages()`

### Examples

```

# Specify list of packages to download
mirror <- c(CRAN = "https://cloud.r-project.org")
pkgs <- c("foreach")

if (interactive()) {
  pdb <- cranJuly2014

  pdb <- pkgAvail(
    repos = c(CRAN = getOption("minicran.mran")),
    type = "source"
  )

  pkgList <- pkgDep(pkgs, availPkgs = pdb, repos = mirror,
    type = "source", suggests = FALSE)
  pkgList

  # Create temporary folder for miniCRAN
  dir.create(pth <- file.path(tempdir(), "miniCRAN"))

  # Make repo for source and win.binary
  makeRepo(pkgList, path = pth, repos = mirror, type = "source")

  # List all files in miniCRAN
  list.files(pth, recursive = TRUE)

  # Check for available packages
  pkgAvail(repos = pth, type = "source")

  # Repeat process for windows binaries
  makeRepo(pkgList, path = pth, repos = mirror, type = "win.binary")
  pkgAvail(repos = pth, type = "win.binary")

  # Delete temporary folder
  unlink(pth, recursive = TRUE)

```

```
}
```

---

pkgAvail

*Reads available packages from CRAN repository.*

---

## Description

This is a thin wrapper around `utils::available.packages()`. If the argument `path` is supplied, then the function attempts to read from a local repository, otherwise attempts to read from a CRAN mirror at the `repos` url.

## Usage

```
pkgAvail(
  repos = getOption("repos"),
  type = "source",
  Rversion = R.version,
  quiet = FALSE,
  filters = NULL
)
```

## Arguments

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>repos</code>    | URL(s) of the 'contrib' sections of the repositories, e.g. " <a href="https://cran.us.r-project.org">https://cran.us.r-project.org</a> ". Passed to <a href="#">available.packages()</a>                                                                                                                                                                                                                                                                              |
| <code>type</code>     | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                                                          |
| <code>Rversion</code> | Version of R (only used if <code>type</code> is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components <code>major</code> and <code>minor</code></li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| <code>quiet</code>    | If TRUE, suppresses warnings                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <code>filters</code>  | passed to <a href="#">utils::available.packages</a>                                                                                                                                                                                                                                                                                                                                                                                                                   |

## See Also

[pkgDep\(\)](#)

---

|        |                                        |
|--------|----------------------------------------|
| pkgDep | <i>Retrieves package dependencies.</i> |
|--------|----------------------------------------|

---

## Description

Performs recursive retrieve for Depends, Imports and LinkLibrary. Performs non-recursive retrieve for Suggests.

## Usage

```
pkgDep(
  pkg,
  availPkgs,
  repos = getOption("repos"),
  type = "source",
  depends = TRUE,
  suggests = TRUE,
  enhances = FALSE,
  includeBasePkgs = FALSE,
  Rversion = R.version,
  quiet = FALSE,
  ...
)
```

## Arguments

|                 |                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkg             | Character vector of packages.                                                                                                                                                                                                                                                                                                                                               |
| availPkgs       | Data frame with an element called package. The package element is a vector of available packages. Defaults to reading this list from CRAN, using <a href="#">available.packages()</a>                                                                                                                                                                                       |
| repos           | URL(s) of the 'contrib' sections of the repositories, e.g. "https://cran.us.r-project.org". Passed to <a href="#">available.packages()</a>                                                                                                                                                                                                                                  |
| type            | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                |
| depends         | If TRUE, retrieves Depends, Imports and LinkingTo dependencies (non-recursively)                                                                                                                                                                                                                                                                                            |
| suggests        | If TRUE, retrieves Suggests dependencies (non-recursively)                                                                                                                                                                                                                                                                                                                  |
| enhances        | If TRUE, retrieves Enhances dependencies (non-recursively)                                                                                                                                                                                                                                                                                                                  |
| includeBasePkgs | If TRUE, include base R packages in results                                                                                                                                                                                                                                                                                                                                 |
| Rversion        | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> </ul> |

- the result of [R.version](#)

quiet            If TRUE, suppresses warnings

...             Other arguments passed to [available.packages\(\)](#)

**Value**

character vector of package names

**See Also**

Other dependency functions: [basePkgs\(\)](#), [makeDepGraph\(\)](#), [plot.pkgDepGraph\(\)](#)

**Examples**

```
if (interactive()) {
  pkgDep(pkg = c("ggplot2", "plyr", "reshape2"),
    repos = c(CRAN = "https://cloud.r-project.org")
  )

  pdb <- cranJuly2014
  pdb <- pkgAvail(repos = c(CRAN = getOption("minicran.mran")))

  pkgDep(pkg = c("ggplot2", "plyr", "reshape2"), pdb)
}
```

---

plot.pkgDepGraph

*Plots a package dependency graph.*

---

**Description**

Plots a package dependency graph.

**Usage**

```
## S3 method for class 'pkgDepGraph'
plot(
  x,
  pkgsToHighlight,
  main = paste(attr(x, "pkgs"), collapse = ", "),
  legendPosition = c(-1.2, -1),
  shape = "circle",
  vertex.size = 8,
  cex = 1,
  ...
)
```

**Arguments**

|                              |                                                                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>               | Object to plot                                                                                                                                                |
| <code>pkgsToHighlight</code> | Optional character vector with names of package to highlight. If missing, defaults to packages used in original call to <a href="#">makeDepGraph()</a>        |
| <code>main</code>            | Title of plot                                                                                                                                                 |
| <code>legendPosition</code>  | Numeric vector of length 2, indicating (x, y) position of edge legend. Both values should be in the range [-1; 1]. If NULL, the edge legend is not displayed. |
| <code>shape</code>           | Shape of edge. See <a href="#">igraph::igraph.plotting()</a> . Could be "none", "circle", "square", ...                                                       |
| <code>vertex.size</code>     | Size of vertex shape. <a href="#">igraph::igraph.plotting()</a>                                                                                               |
| <code>cex</code>             | Vertex label size.                                                                                                                                            |
| <code>...</code>             | Ignored                                                                                                                                                       |

**See Also**

Other dependency functions: [basePkgs\(\)](#), [makeDepGraph\(\)](#), [pkgDep\(\)](#)

**Examples**

```
tags <- "chron"

# Plot using defaults

if (interactive()){
  pdb <- pkgAvail(
    repos = c(CRAN = getOption("minicran.mran")),
    type = "source"
  )
} else {
  pdb <- cranJuly2014
}

if (interactive()) {
  dg <- makeDepGraph(tags, availPkgs = pdb , includeBasePkgs = FALSE,
    suggests = TRUE, enhances = TRUE)

  set.seed(43);
  plot(dg)

  # Move edge legend to top left
  set.seed(42);
  plot(dg, legendPosition = c(-1, 1))

  # Change font size and shape size
  set.seed(42);
  plot(dg, legendPosition = c(-1, 1), vertex.size = 20, cex = 0.5)
```

```
# Move vertex legend to top right
set.seed(42);
plot(dg, legendPosition = c(1, 1), vertex.size = 20, cex = 0.5)
}
```

---

repoPrefix

*Get the path to the repo directory containing the package files.*


---

## Description

Get the path to the repo directory containing the package files.

## Usage

```
repoPrefix(type, Rversion)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type     | character, indicating the type of package to download and install. See <a href="#">install.packages()</a> .                                                                                                                                                                                                                                                                                                                    |
| Rversion | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |

## Value

The file path to the package files directory.

## Repo folder structure

A repository has two main folders, one for source packages, and the other for binary packages. Inside the binary package folder, bin, you will find subfolders for Windows as well as the various OSX binaries.

```
+-- Root
...+-- src/contrib
.....+-- PACKAGES
..+-- bin
.....+-- windows/contrib/version
.....+-- PACKAGES
.....+-- macosx/contrib/version
```

```

.....+- PACKAGES
.....+- macosx/mavericks/contrib/version
.....+- PACKAGES
.....+- macosx/leopard/contrib/version
.....+- PACKAGES

```

**Note**

Not all versions of R are compatible with with all package types (e.g., `mac.binary.el-capitan` is only valid for `R > 3.4.0`).

---

|                  |                                                 |
|------------------|-------------------------------------------------|
| twodigitRversion | <i>Get a two-digit version of the R version</i> |
|------------------|-------------------------------------------------|

---

**Description**

Get a two-digit version of the R version

**Usage**

```
twodigitRversion(Rversion = R.version)
```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rversion | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components <code>major</code> and <code>minor</code></li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Value**

A character string representing the two-digit R version.

---

updatePackages

---

*Check for available package updates in a miniCRAN repo.*


---

## Description

oldPackages() indicates packages which have a (suitable) later version on the repositories whereas updatePackages() offers to download and install such packages.

## Usage

```
oldPackages(
  path = NULL,
  repos = getOption("repos"),
  availPkgs = pkgAvail(repos = repos, type = type, Rversion = Rversion),
  method,
  availableLocal = pkgAvail(repos = path, type = type, Rversion = Rversion, quiet =
    quiet),
  type = "source",
  Rversion = R.version,
  quiet = FALSE
)

updatePackages(
  path = NULL,
  repos = getOption("repos"),
  method = NULL,
  ask = TRUE,
  availPkgs = pkgAvail(repos = repos, type = type, Rversion = Rversion),
  oldPkgs = NULL,
  type = "source",
  Rversion = R.version,
  quiet = FALSE
)
```

## Arguments

|                |                                                                                                                                                                                                                           |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| path           | Destination download path. This path is the root folder of your new repository.                                                                                                                                           |
| repos          | URL(s) of the 'contrib' sections of the repositories, e.g. "https://cran.us.r-project.org". Passed to <a href="#">available.packages()</a>                                                                                |
| availPkgs      | Data frame with an element called package. The package element is a vector of available packages. Defaults to reading this list from CRAN, using <a href="#">available.packages()</a>                                     |
| method         | Download method, see <a href="#">download.file()</a> .                                                                                                                                                                    |
| availableLocal | all packages hosted in the miniCRAN repo, as returned by <a href="#">pkgAvail()</a> . A subset can be specified; currently this must be in the same (character matrix) format as returned by <a href="#">pkgAvail()</a> . |

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type     | Possible values are (currently) "source", "mac.binary" and "win.binary": the binary types can be listed and downloaded but not installed on other platforms. Passed to <a href="#">download.packages()</a> .                                                                                                                                                                                                                   |
| Rversion | Version of R (only used if type is not source.) Defaults to <a href="#">R.version</a> , but this can be specified as any of the following formats: <ul style="list-style-type: none"> <li>• a character string with the two digit R version, e.g. "3.1"</li> <li>• a list with components major and minor</li> <li>• the result of <a href="#">getRversion()</a></li> <li>• the result of <a href="#">R.version</a></li> </ul> |
| quiet    | If TRUE, suppress status messages (if any), and the progress bar during download.                                                                                                                                                                                                                                                                                                                                              |
| ask      | logical indicating whether to ask user before packages are actually downloaded and installed. Alternatively, the value "graphics" starts an interactive widget to allow the user to (de-)select from the list of packages which could be updated or added. The latter value only works on systems with a GUI version of <a href="#">select.list()</a> , and is otherwise equivalent to ask = TRUE.                             |
| oldPkgs  | if specified as non-NULL, <a href="#">updatePackages()</a> only considers these packages for updating. This may be a character vector of package names or a matrix as returned by <a href="#">oldPackages()</a> .                                                                                                                                                                                                              |

### Details

These functions are based on [update.packages\(\)](#). However, rather than looking for locally installed packages they look for the package source and binaries in the miniCRAN repository.

### Value

[oldPackages\(\)](#) returns a matrix with one row per package and columns for "Package", "LocalVer", "ReposVer" and "Repository". The matrix row names the package names.

[updatePackages](#) returns NULL invisibly.

### See Also

[updatePackages\(\)](#), [pkgAvail\(\)](#).

Other update repo functions: [addOldPackage\(\)](#), [addPackage\(\)](#), [checkVersions\(\)](#), [makeRepo\(\)](#)

### Examples

```
### `oldPackages` and `updatePackages` require an existing miniCRAN repo

# Specify list of packages to download
mirror <- c(CRAN = "https://cloud.r-project.org")
pkgs <- c("foreach")

pdb <- cranJuly2014

if (interactive()) {
```

```
pdb <- pkgAvail(repos = mirror, type = "source")

pkgList <- pkgDep(pkgs, availPkgs = pdb, repos = mirror, type = "source", suggests = FALSE)
pkgList

# Create temporary folder for miniCRAN
dir.create(pth <- file.path(tempdir(), "miniCRAN"))

# create the miniCRAN directory structure but only add bin files
makeRepo(pkgList, path = pth, repos = mirror, type = "source", download = FALSE)
makeRepo(pkgList, path = pth, repos = mirror, type = "win.binary", download = TRUE)

# download old source package version and create repo index
oldVers <- data.frame(package = c("foreach", "codetools", "iterators"),
                      version = c("1.4.0", "0.2-7", "1.0.5"),
                      stringsAsFactors = FALSE)
addOldPackage(pkgList, path = pth, repos = mirror, vers = oldVers$version, type = "source")
# NOTE: older binary versions would need to be build from source

# Check if updated packages are available
oldPackages(path = pth, repos = mirror, type = "source") # should need update
oldPackages(path = pth, repos = mirror, type = "win.binary") # should be current

# Update available packages
updatePackages(path = pth, repos = mirror, type = "source", ask = FALSE) # should need update
updatePackages(path = pth, repos = mirror, type = "win.binary") # should be current

# Delete temporary folder
unlink(pth, recursive = TRUE)
}
```

# Index

- \* **Internal**
  - .listFiles, 4
  - repoPrefix, 25
  - twodigitRversion, 26
- \* **create repo functions**
  - pkgAvail, 21
- \* **datasets**
  - cranJuly2014, 15
- \* **dependency functions**
  - basePkgs, 12
  - makeDepGraph, 16
  - pkgDep, 22
  - plot.pkgDepGraph, 23
- \* **github functions**
  - addPackageListingGithub, 11
- \* **package**
  - miniCRAN-package, 2
- \* **update repo functions**
  - addOldPackage, 6
  - addPackage, 9
  - checkVersions, 13
  - makeRepo, 18
  - updatePackages, 27
- .listFiles, 4
- addLocalPackage, 5
- addOldPackage, 6, 10, 13, 20, 28
- addPackage, 7, 9, 13, 20, 28
- addPackageListingGithub, 11
- available.packages(), 7, 9, 12, 15, 17, 19, 21–23, 27
- basePkgs, 12, 17, 23, 24
- checkVersions, 7, 10, 13, 20, 28
- cranJuly2014, 15
- download.file(), 27
- download.packages(), 5, 7, 9, 15, 17–19, 21, 22, 28
- getCranDescription, 15
- getRversion(), 5, 7, 9, 13, 19, 21, 22, 25, 26, 28
- igraph::igraph.plotting(), 24
- install.packages(), 13, 25
- is.online, 16
- makeDepGraph, 12, 16, 23, 24
- makeDepGraph(), 3, 24
- makeLibrary, 18
- makeRepo, 7, 10, 13, 18, 28
- makeRepo(), 3
- miniCRAN (miniCRAN-package), 2
- minicran (miniCRAN-package), 2
- miniCRAN-package, 2
- oldPackages (updatePackages), 27
- oldPackages(), 3
- pkgAvail, 21
- pkgAvail(), 3, 12, 27, 28
- pkgDep, 12, 17, 22, 24
- pkgDep(), 3, 12, 17, 21
- plot.pkgDepGraph, 12, 17, 23, 23
- plot.pkgDepGraph(), 3
- R.version, 5, 7, 9, 13, 19, 21–23, 25, 26, 28
- repoPrefix, 25
- select.list(), 28
- twodigitRversion, 26
- update.packages(), 28
- updatePackages, 7, 10, 13, 20, 27
- updatePackages(), 3, 28
- updateRepoIndex (makeRepo), 18
- utils::available.packages, 19, 21
- utils::available.packages(), 3, 15, 21
- utils::download.packages(), 20

`utils::install.packages()`, [3](#), [18](#)

`utils::installed.packages()`, [12](#)

`write_PACKAGES()`, [5](#), [7](#), [9](#), [19](#), [20](#)